

VCOM PRODUCT CATALOG



Contents

Creator's Command Center	
High-speed Transfer Series Wireless Screencast Extender Micphone & Camera Accessories	3
Next Charging Solution Travel Charger Wireless Charging Station	
Next Gen Workspace Keyboard & Stream Dock Al Translation TWS FindMy Series	10
Hot Sale & New Arrivals USB4 Cable HDMI Adapter DP Cable & Adapter	17



YOUR FINGER IS YOUR KEY Fingerprint Encryption SSD Enclosure

CU855SN-F











Tool-free installation

M.2 NVMe SSD Enclosure with Fingerprint Access

Protocol: NVMe & SATA USB Version USB 3.2 GEN2 Data Transfer Speed: Up to10Gbps Max Capacity: 8TB SSD Compatibility: M.2 NVMe M Key&B+M Key SSD Supported SSD SIZE: 2230/ 2242/2280 Power Retention Time: <1s LED Indicators Power indicator, Operating status indicator Encrypted: Fingerprint Encryption Compatible system :Windows, Mac OS, Android material Aluminum Shell



CU874N











USB4 M.2 NVMe SSD Enclosure

USB4 SSD Enclosure for M.2 PCI-E NVME Protocol 40G Supported SSD SIZE:2280 Color Gray, material Aluminum Shell



CU875N











Thunderbolt 5/USB4 V2.0 Compatible 80Gbps M.2 NVMe SSD Enclosure

Color: Grav Host Connectors: 1x USB Type-C Material: Aluminum Alloy Plug and Play: Yes Cable Type: Type-C to Type-C Data Transfer Speed: 80Gbps Compatibility: Thunderbolt 4/3, USB4 Built-in Silent Fan: Yes Compatible Systems: Windows, Mac OS, Android



CU856N













Tool-free

Magnetic Portable SSD

Port Type: USB Type-C Data Transfer Speed: Up to 20 Gbps Cable Type: USB-C to USB-C Power Requirement: 5V Material: Aluminum Shell Compatibility: iOS, Windows, Android, macOS

USB Version: USB 3.2 Gen2x2 Storage: 512GB.1TB. 2TB Cable Length: 65mm Plug and Play: Yes



CU876N















Color: Gray Host Connectors: 1x USB Type-C Plug and Play: Yes Material: Aluminum Allov Cable Type: Type-C to Type-C Built-in Silent Fan: Yes Compatible Systems: Windows, Mac OS, Android Data Transfer Speed: 80Gbps, 10Gbps

(When connected to a non-Thunderbolt USB-C Host) Compatibility: Thunderbolt 4/3, USB4/USB3.2Gen2





DD545-TH



1080P ScreenCast

Material: Plastic Maximum ReChip: 1080P@60Hz (Note: The original "1080P60" is standardized to "1080P@60Hz", a common format in display and transmission specs where "@60Hz" clearly indicates the 60Hz refresh rate corresponding to 1080P reChip.)

Connection: Supports up to 8 Transmitters (TX) paired with 1

Receiver (RX)
Range: 50 Meters in Open, Unobstructed Areas
Connectors: TX-HDMI, RX-HDMI
TX PD Max: 60W

(supports up to 60W charging for connected devices)

DD547



4K ScreenCast

Function key display screen Material: Plastic Maximum reChip: 4K 30Hz Connection: Supports up to 8 transmitters (TX) to 1 receiver (RX)
Distance: 50 meters in open space without obstruction
Connector: TX-HDMI, RX-HDMI (Requires USB-C female port to be plugged in for power supply) Supports 8 transmitters to 1 receiver



M906

Mini Wireless Lavalier Microphone

Input Voltage: 5V Microphone Battery Capacity: 60mAh Battery Charging Case Capacity: 300mAh Lithium Battery Microphone Polar Pattern: Omnidirectional Battery Life: 5-6 Hours Signal-to-Noise Ratio (SNR): 70dBm Transmission Latency: 30ms Sensitivity: -42dB Frequency Response Range: 20-20kHz Transmission Distance: 40-50 Meters (Unobstructed) Single Unit Weight: 52a Whole Set Weight: 100g













M902B

USB RGB Microphone with Boom Arm

Pointing Heart shaped pointing Frequency Response 30-20KHz Sensitivity -40 dB±3dB Signal-to-Noise Ratio > 79dB Sampling Rate 48kHz-192kHz Compatible Systems Windows, Android, macOS Pop Filter Included RGB Lighting Support Port USB 2.0 TYPE-C Female Cable length 1.8m Cable Type USB-ATO USB-C Cable Power Source DC 5V Weight 0.5 kg









M907

Mini Wireless Lavalier Microphone

Input Voltage: 5V Battery Capacity: 80mAh Lithium Battery Charging Case Battery: 600mAh Battery Life: 4-5 Hours Signal-to-Noise Ratio (SNR): 64dBm Transmission Latency: 30ms Sensitivity: -42dB Frequency Response Range: 20-20kHz Transmission Distance: 40-50 Meters















M723

Auto Face Tracking Tripod 360° Rotating Kits Stand

Material: ABS (Stainless Steel) Supports phone sizes 65-90cm Follow-up camera battery: 18650 polymer Follow-up camera battery capacity: 1800 milliampere Battery working time: 5-7 hours Remote control battery: 402025 polymer Remote control battery capacity: 150 milliampere Number of boxes per set: 80PCS Accessories: Instruction manual*1, Charging cable*1 Spotlight battery: 401020 Battery capacity: 55 milliampere Usage time: 1-2 hours Lighting modes: Warm light/Cold light/Flexible light



USB RGB Microphone

"Microphone capsule size: 14mm Polar Pattern/Frequency Response: 40-18,000Hz Sensitivity: -37 dBV/Pa Maximum SPL: 124 dB (THD < 1% @ 1kHz) Signal-to-Noise Ratio (SNR): 80 dB Power Supply: USB Power Supply (5V DC) Bit Depth: (16bit) / (24bit @ Windows 10) Recording Sample Rate: 48/96/192KHz Playback Sample Rate: 48KHz Stereo Total Harmonic Distortion (THD): < 0.8% Compatible Systems: Apple (macOS/iOS), Android, Windows, Linux











M952

Vlog Selfie Monitor Screen

- Display Size: 3.97inches (IPS panel, diagonal)
 Screen ReChip: 480 × 800 pixels (W × H), 16:9 aspect ratio
- ·Brightness: ~250cd/m2 (typical)
- . Contrast Ratio: 700:1 (typical)
- Refresh Rate: 60Hz Color Gamut: 16.7K colors
- (60% NTSC coverage) Connector(s):
- Type-C ×1 (power input only, 5V/1A) USB-C video input port
- (supports USB-C display-out)
- 1×Power ON/OFF 1×Aspect-ratio toggle
- 1×Screen flip
- (landscape/portrait rotation) 1×Brightness adjust
- Battery: Built-in 1500mAh polymer battery, ~3 hours runtime (wireless mode) Compatibility:iOS ≥9.0 — Android ≥2.0 — HarmonvOS ≥3.0 — MagicOS ≥4.0 (eleven systems in total)



M-HHT907

Universal Travel Adapter, International Power Adapterwith Built-in Retractable USB-C Cable

Input: 100V - 240V AC, 50/60Hz Rated power: 100V - 240V AC, 10A Max, 1000W - 2400W 5-port fast charging with 2 USB-A QC 18W + 2 USB-C PD 20W

USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A (45W Max) USB-C2/C3: 5V/3A, 9V/2.22A, 12V/1.67A (20W Max) USB-A1/A2: 5V/3A, 9V/2A, 12V/1.5A (18W Max) Protection functions (short circuit protection, overcurrent protection, input fuse) Yes

Available plugs: British standard / American standard / European standard / Australian standard



M-A19

72W car Charger with Built-in Retractable USB-C Cable

- Housing Material
 DC 12V-24V.
 Output Interfaces & Specifications
- QC3.0 Port
- * Max Output: 18W * Protocol: QC3.0 * Output: 5V/3A, 9V/2A, 12V/1.5A

- Output: 5V/3A, 9V/3A, 12V/2.5A
 PPS: 3.3V–11V/3A (Provides dynamic voltage adjustment for superior compatibility and efficiency).
- Type-C Extension Cable Port (With an integrated ~70cm / 2.3 ft cable) * Max Output: 30W * Protocols: PD3.0, PPS
 * Output: 5V/3A, 9V/3A, 12V/2.5A * PPS: 3.3V-11V/3A
 4. Total Power Output • Maximum Combined Output: 72W
- * Important Note on Simultaneous Use: When the QC port and the PD port are

used at the same time, their combined output will be limited to 5V/3A (15W total). 5. Extension Cable • Length: Approximately 70cm (2.3 feet)



Retractable USB-C Cable with adapter kit

Material: Aluminum Allov + ABS + TPE Colors: Black, White Wire gauge: 55/0.08TC*2C + 16/0.08TC*3C

1. Type-c to Type-c Cable, L = 100CM (20V/3A 60W MAX); 2. Type-c to Micro Adapter (5V/2.4A MAX)

3. Type-c to Lightning Adapter (5V/2,4A)

4. USB to Type-c Adapter (5V/2.4A MAX)

5. USB to Type-Lightning Adapter 6. USB to Type-Micro Adapter

7. Card Puller

8. Mobile Phone Stand

Function: Data transmission and charging synchronization Type-c to Type-c :480Mbps



M-HHT907 GaN100W

Universal Travel Adapter, International Power Adapterwith Built-in Retractable USB-C Cable

Material: PC Input: 100V - 240V AC, 50/60Hz Rated power: 100V - 240V AC, 10A Max, 1000W - 2400W 5-port fast charging: 2 USB-A QC 18W + 2 USB-C PD 20W + 1 USB-C PD 100W USB-C1:5V/3A,9V/3A,12V/3A, 15V/3A.20V/5A(100W Max) USB-C2/C3: 5V/3A. 9V/2.22A, 12V/1.67A (20W Max)
USB-A1/A2: 5V/3A. 9V/2A. 12V/1.5A (18W Max)
Protection functions (short circuit protection, overcurrent protection, input fuse); Yes Available plugs: British standard / American standard / European standard / Australian standard Product dimensions: 92x56x56mm



M173

Watch Charger with adapter kit

Material: ABS + PVC Colors: Black

Wire specification: 55/0.08TC*2C + 16/0.08TC*3C 1. Type-c to Type-c cable, L = 28CM (20V/3A 60W MAX);

- 2. Type-c to Lightning adapter (5V/2.4A);
- 3. USB to Type-c adapter (5V/2.4A MAX);
- 4. USB to Type-Lightning adapter;
- 5. Card removal tool: 6. SIM card slot:
- 7. Apple Watch wireless charging
- Function: Data transmission and charging synchronization Type-c to Type-c :480Mbps



M175

USB-C Adapter Kit with Travel Case

Core Specifications (Shared Across Most Adapters): Transmission Bandwidth: 40 Gbps (USB4 v2.0) Max Power Delivery: 240W Max Video Support: 8K @ 60Hz Material: Aluminum Case (Space Gray) Connector: Stainless Steel with Nickel Plating Included Adapter: USB4 U-Shape Male-to-Male Adapter x 1 USB4 U-Shape Male-to-Female Adapter × 1 USB4 L-Type Male-to-Female Adapter × 3 USB4 Standard Male-to-Female Adapter x 1 Note: This unit supports 10 Gbps and 60W power USB-A Male to USB-C Female Adapter × 1 Speed: USB-C side: 10 Gbps | USB-A side: 480 Mbps Power: 60W USB4 240W Short Cable (0.13m) × 1





M171

Magnetic Wireless Charger with Cleaning Kit

Complies with CE, ROHS, FCC certifications Applicable Models Charging Protocol PD Charger applicable form 2 Wireless charging Plug standard Output power current total power 15W Output current 1.67A Maximum output power 15W Connector type:TYPE-C Output power 15W Color:black



M172

Magnetic Travel Charging Station with adapter kit

Material: ABS + PVC
Wire gauge: 55/0.08Tc*2C + 16/0.08TC*3C
1. Type-c to Type-c cable, length 28CM (20V/3A 60W MAX);
2. Type-c to Lightning adapter (5V/2.4A);
3. USB to Type-c adapter (5V/2.4A MAX)
4. USB to Type-Lightning adapter
5. Card removal tool
6. Phone stand
7. SIM card sold
7. SIM card sold

 S. Apple Watch wireless charging (2.5W)
 Phone wireless charging 15W
 O. Headphone wireless charging 5W Function: Data transmission and charging are synchronized. Net weight: 105g



Make Data Entry & Calculations Easier

2 in 1 Wireless Calculator Numeric Keypad



DK513















34 Keys Battery 2.4G Dual Durability Layout -Mode

One-touch Switching

BT & 2.4G 2-in-1 Dual-Mode Keyboard Calculator

Solutions: BK3633 QFN40 Screen Driver: TM1621 SOP48 Wireless: BT 5.0 + 2.4G dual mode Number of Keys: 34 keys Asynchronous or Not: Yes One-click Upload of Calculation Results Supported Systems: Windows, iOS, Android, Mac Os









CUE41

Stream hub with trigger actions screen

Stream Dock Visual Expansion Dock

- I. All-in-One Expansion Dock 1. Type-C (PD) Connector: Supports up to 100W fast charging(reserve 15
- watts, Actual charging to host is 85w) 2. HDTV: Maximum reChip is 3840*2160
- 3. RJ45 Connector: Adaptive 10/100M Ethernet
- 4. SD/TF Connector: Compatible with SD or TF card reading and writing (*SD card/TF card cannot work simultaneously)
- 5. USB 3.0; Maximum transmission bandwidth up to 5.0Gbps
- II. Custom Touch Screen
- 1.3*4 custom touch screen buttons
- 2. DIY macro command icons 3. Custom layout
- 4. Three modes: Screen saver mode, button mode, GIF display mode



M620

Stream Deck Studio Controller

Product Name: Visual Custom Control Console MBox N3

I. Basic Configuration Parameters: Number of Buttons: 6 Operating Voltage/Current: 5V/0.6A

Connection Method: Wired Backlight: LCD

II. Product Dimensions: 131*80.2*68.4 mm

Weight: 156a

Keycap Material: Acrylic

Top/Bottom Cover/Positioning Plate Material: ABS Axis Information: Silicone

Knob Material: Aluminum Alloy

III. Included Accessories * Quantity MBox N3*1 USB 2.0 Type-A to Type-C Cable *1 Instruction Manual *1

Cable Length: 1.5m

IV. Supported Operating Systems:Windows 7 64-bit and abovemacOS 10.15 and above



DK405

Matrix: Full-key no bump

Mechanical Keyboard with trigger actions screen

Product Brand: MiraBox Product Model: K1 Pro Connection Method: USB Wired Connector Type: Separate cable Type C Connector Product Dimensions: Keyboard: 386X146X43mm: Lighting Effects: 11 types of ARGB lighting Number of Keys: 78 keys + 3 knobs + 6 visual keys

Supported Systems: Windows 7 64-bit and above; macOS 10.15 and above



DK215

Wireless Keyboard and Mouse Combo

1.BT + 2.4G wireless range: 10m

2.Key number: 105 keys 3.Color: Space Gray

4.Port: Type-C

5.Voltage/current: 3.7V / 3mA (MAX)

6.Battery capacity: 400mAh 7.Net weight: 480g ±5g

8. Material: ABS / Plastic panel 9. System compatibility: Windows. macOS,Android

10.Glow mode: No backlight 11.Size: 384 * 130 * 18mm

1.BT + 2.4G wireless range: 10m 2.DPI: 1200 3.Buttons: 3 keys

4. Color: Space Grav

5.Size: 109.2 * 60 * 30.2mm 6.Net weight: 63g

7.Material: ABS 8.Voltage/current: 3.7V / 15mA 9.Battery: 500mAh













AI-Powered Translation Meets Active Noise Cancellation.



ANC Noise Reduction27dB



Al Multi-function **Translation**



Touch Button





M202AE

Active Noise Cancelling Wireless Earbuds

[Function] FF + FB Hybrid FeedBack 6 pieces. Half-ear ANC adaptive noise reduction 25-30dB Call noise reduction + Transparent mode / Noise reduction adaptive mode / Normal mode / Hall / Battery level display

Bluetooth Chip. Version] Jerry 7016G / 5.4
[Earphone Battery] 450903 30mAh
[Charging Case Battery] 701535 400mAh (with protective cover) Speaker Full-range speaker 013mm@32 ohm

[Music Playback Time] 4-5 hours [StandBy Time] 150 hours Noise Reduction Depth] -30dB

[Call Time] 3-4 hours [Bluetooth Range] 10m [Net Weight per Unit] 47g Surface Treatment/Material1 Electroplating / ABS













M203AE

Active Noise Cancelling Wireless Earbuds with AI translate

[Function] FF + FB Hybrid FeedBack

6-microphone ANC adaptive noise reduction 27-30dB ENC call noise reduction + ANC adaptive noise reduction + normal mode / Hall switch

[Bluetooth Chip. Version] Jerry 7016G / Compatible with 5.4 [Earphone Battery] 450909 / 30mAh

[Charging Case Battery] 701535 / 400mAh (with protective cover) [Speaker] Titanium membrane full-range speaker Ф13mm @ 32 ohm [Music Playback Time] 5 hours [Call Time] About 4 hours Stand By Timel 150 hours [Noise Reduction Depth] -27dB [Surface Treatment/Material] Sand Blasted / Electroplated / ABS [Box Size] 11 * 8.3 * 3.5cm Net weight: 46g Single net weight: 4g













NLT-10A



Apple FindMy

Smart Tag,4pc/pack

Standby time: 10-12 months (typical usage)

Wireless Range: ≥ 40m (open line of sight)

Anti-lost device

Battery: CR2032

Buzzer: >75 dB

APP: FindMy

Battery voltage: 3V









battery life

long-distance Global positioning





Ultra-long

tracking

F15PC

Work with Apple FindMy

Findmy Card

- 1. Ultra-thin, with a thickness of 1.5 millimeters. thinner than two bank cards.
- 2. IP68 waterproof and durable.
- 3. Wireless charging 4. Global positioning
- 5. No need for SIM card or APP fees.
- 6. Apple MFI certification.
- 7. Optional colors: black, customizable colors.
- *Telink domestic chip.
 *Cold pressing process card.
 *Supports IOS.

- *Wireless charging battery,
- the battery can work for 1-2 months after each charge.





MC13









Ultra-long



Work with Apple FindMy





Findmy Wallet

- MagSafe wireless charging
 Global positioning, reminder for lost items
- 3. Strong and durable hinge, can be smoothly opened to any angle Degree
- 4. It is both a card holder and a multi-angle support device
- 5. Equipped with powerful magnets, it can provide stable support at any angle 6. 2 slots can accommodate 2-3 cards
- 7. No SIM card required, no APP fees
- 8. Apple MFI certified
- 9. Available colors: black, brown, customizable colors

10. Size: 9.5cm * 6.5cm



MC03











Work with Apple FindMy





Findmy Wallet

- MagSafe Wireless Charging
 Global Positioning Reminder for Lost Items
 Rotating Cover Design Large Capacity
- 4. Both Card Holder and Stand
- 5. Built-in Strong Magnet Securely Stabilized with a Single Pull
- 6. Two Card Slots Can Hold 2-3 Cards 7. No SIM Card Required, No App Fee
- 8. Apple MFI Certified
- 9. Optional Colors: Black, Brown, Customizable Colors
- 10. Size: 9.5cm * 6.5cm
- 11. PU + Rotating Shaft + Magnet + Iron Sheet + Spring Piece + PC

Hot-sale

& New Arrivals









CU580M









USB-C 80Gbps USB4 Cable

Material: Aluminum shell+Nickel Plated plug Data transfer: 80Gbps USB4, Power: Built in E-Marker Chip support 240W/ 100W.

Video: Dual screens at 8K@60Hz, Single screen at 16K@60Hz. Compatible with Thunderbolt 4/3, USB3.2 & 3.1 Transfer protocol Function: Charge, Data Transfer, Video, Audio



CU582









USB4 V2.0 240W Cable

TYPE-CM/CM Full-Function High-Speed Flat Cable Bandwidth: 80Gbps Maximum video resolution: 8K@60Hz Keychain design 240W | Aluminum Shell + TPE Jacket, Nickel-Plated



CU582RC











USB4 V2.0 240W L-Type Cable

TYPE-CM/CM Straight-to-Right-Angle 90° Full-Function High-Speed Flat Cable Bandwidth: 80Gbps Maximum video resolution: 8K@60Hz L=0.13m240W | Aluminum Shell + TPE Jacket, Nickel-Plated



CU583











USB4 V2.0 240W Extension Cable

TYPE-CM/CF Full-Function High-Speed Flat Extension Cable Bandwidth: 80Gbps Maximum video resolution: 8K@60Hz 240W | Aluminum Shell + TPE Jacket, Nickel-Plated



CU581











USB4 V2.0 240W Cable Portable Keychain

TYPE-CM/CM Full-Function High-Speed Flat Cable Bandwidth: 80Gbps Maximum video resolution: 8K@60Hz Keychain design L=0.2m 240W | Aluminum Shell + TPE Jacket, Nickel-Plated



CU582RA













USB4 V2.0 240W L-Type Cable

TYPE-CM/CM Straight-to-Center-Symmetrical 90° Full-Function High-Speed Flat Cable Bandwidth: 80Gbps Maximum video resolution: 8K@60Hz 240W | Aluminum Shell + TPE Jacket, Nickel-Plated



CU582RD













USB4 V2.0 240W L-Type Cable

TYPE-CM/CM Straight-to-Right-Angle 90° Full-Function High-Speed Flat Cable Bandwidth: 80Gbps Maximum video resolution: 8K@60Hz 240W | Aluminum Shell + TPE Jacket, Nickel-Plated



CU545











Fast Charging Protocols: PD3.1, PD3.0, QC4+, PPS

Connector Type: TYPE-C (Male/Male) Coaxial Design, Nickel-Plated Self-Coiling via Magnetic Cable Length: 1 m Data Transmission: Thunderbolt 4 & USB4 Dual Protocol Support, 40Gbps (Gen 3) Video Support: DP Alt Mode (8K@60Hz, 4K@120Hz) Power Delivery: PD 3.1 EPR, 240W (50V/5A)





CA353

HDMI 2.1 Female to Female Extension Coupler/Adapter

Connector Type: HDMI Female to HDMI Female (Type A) HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD. Dynamic HDR. Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Alloy Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required Compatible Devices: PS5, Xbox Series X/S, 8K TVs,

CA354RA

HDMI 2.1 Male to Female upright L-Type Extension Coupler/Adapter

4K@120Hz gaming monitors, soundbars, AV receivers

Connector Type: HDMI Male to HDMI Female upright (Type A) Straight-to-Right-Angle 90° HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps
Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Alloy Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz gaming monitors, soundbars, AV receivers

CA355

Micro HDMI 2.1 Male to HDMI Female Adapter

Connector Type: Micro HDMI Male to HDMI Female HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR, Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Alloy Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz gaming monitors, soundbars, AV receivers

CA354RC

gaming monitors, soundbars, AV receivers

HDMI 2.1 Male to Female L-Type Extension Coupler/Adapter Connector Type: HDMI Male to HDMI Female upright (Type A) Straight-to-Center-Symmetrical 90° HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Max. Resolution: 8K@60Hz. 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Alloy Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz

CA354

HDMI 2.1 Male to Female Extension Coupler/A

Connector Type: HDMI Male to HDMI Female (Type A) HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR, Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Alloy Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required Compatible Devices: PS5. Xbox Series X/S, 8K TVs, 4K@120Hz

CA354RB

gaming monitors, soundbars, AV receivers

HDMI 2.1 Male to Female reversed L-Type Extension Coupler/Adapter

Connector Type: HDMI Male to HDMI Female reversed (Type A) Straight-to-Right-Angle 90 HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR, Dolby Vision, Supported Patines: 8k Oira HD, Dynamic HDR, Dolby eARC (Enhanced Audio Return Channel)
Housing Material: High-Quality Black Aluminum Alloy
Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required

CA356

Mini HDMI 2.1 Male to HDMI Female Adapter

gaming monitors, soundbars, AV receivers

Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz

Connector Type: Mini HDMI Male to HDMI Female HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR, Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Alloy Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz

CA354RD

gaming monitors, soundbars, AV receiversdard)

HDMI 2.1 Male to Female L-Type reversed Extension Coupler/Adapter

Connector Type: HDMI Male to HDMI Female reversed (Type A) Straight-to-Center-Symmetrical 90° HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR, Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Alloy Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required

Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz gaming monitors, soundbars, AV receivers

CA352





HDMI 2.1 Female to Female Extension Coupler/Adapter

Connector Type: HDMI Female to HDMI Female (Type A) HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps

Max. Resolution: 8K@60Hz, 4K@120Hz Max. resolution: one-douts, and reons Supported Features: 8K Ultra HD, Dynamic HDR, Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper
Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference

Operation: Plug and play, no driver required Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz gaming monitors.

soundbars, AV receivers



CA358







Mini HDMI 2.1 Male to HDMI Female Adapter

Connector Type: Mini HDMI Male to HDMI Female HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Bandwidn: 48 subps Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR, Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum Connector Plating: 24K Gold-Plated Connectors Comhector Flating: -4A Dominectors
(Anti-corrosion, improved signal stability)
Internal Wiring: High-punit stability
Internal Wiring: High-punit layer shield oxygen-free copper
Shieldil: Will-layer shielding (foil + braiding) against EMI/RFI interference
Operation: Plug and pluf sylvery oxygeners
Compatible Devices: PSS, Xob Series X/S, 6K TVs, 4K@120Hz



CA455





gaming monitors, soundbars, AV receivers

USB-C Female to HDMI 2.1 Male Adapter

Connector Type: USB Type-C (Female) to HDMI (Male) Video Resolution: Up to 8K@60Hz Chip:CH7218A Housing: Aluminum Protocol: Compliant with DisplayPort Alt Mode, USB Type-C Specification 1.4 and HDMI 2.1 Plug & Play: No Driver Required, Hot-Pluggable



CA357





HDMI 2.1 Male to Female Extension Coupler/Adapter

Connector Type: HDMI Male to HDMI Female (Type A) HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps Max. Resolution: 8K@60Hz, 4K@120Hz Supported Features: 8K Ultra HD, Dynamic HDR,

Dolby Vision, eARC (Enhanced Audio Return Channel)
Housing Material: High-Quality Black Aluminum
Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity oxygen-free copper
Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference

Operation: Plug and play, no driver required Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz gaming monitors.

soundbars, AV receivers

CA359





Micro HDMI 2.1 Male to HDMI Female Adapter

Connector Type: Micro HDMI Male to HDMI Female HDMI Version: HDMI 2.1 (Fully backward compatible with HDMI 2.0, 1.4, etc.) Bandwidth: 48 Gbps
Max. Resolution: 8K@60Hz, 4K@120Hz
Supported Features: 8K Ultra HD, Dynamic HDR,
Dolby Vision, eARC (Enhanced Audio Return Channel) Housing Material: High-Quality Black Aluminum nousing wateria: high-rouality black xuliminum Connector Plating: 24K Gold-Plated Connectors (Anti-corrosion, improved signal stability) Internal Wiring: High-purity sygen-free copper Shielding: Multi-layer shielding (foil + braiding) against EMI/RFI interference Operation: Plug and play, no driver required Compatible Devices: PS5, Xbox Series X/S, 8K TVs, 4K@120Hz

CA459





gaming monitors, soundbars, AV receivers

USB-C Male to HDMI 2.1 Female Adapter

Connector Type: USB Type-C (Male) to HDMI (Female), Video Resolution: Up to 8K@60Hz Chip:CH7218A Housing: Aluminum Protocol: Compliant with DisplayPort Alt Mode, USB Type-C Specification, and HDMI 2.1 Plug & Play: No Driver Required, Hot-Pluggable





CG635F







Display port M/F 1.4V Extension

Connector 1: DP A Male Connector 2: DP A Female

Bandwidth up to 32GBps 8K@60Hz/4K@120Hz Support HBR3,HDCP2.2/CEC/EDID

Gold plated,Silver Metal Shell, Black cotton net braid



CA351



DP 1.4 Male to HDMI 2.1 Female Adapter

Connector Type: DisplayPort (Male) to HDMI (Female) Video Resolution: Up to 8K@60Hz Chip: CH7218A





CG685F





Mini DP/M to DP/F 1.4V Extension

Connector 1: Mini DP Male Connector 2: DP Female

Bandwidth:32GBps 8K@60Hz/4K@120Hz SupportHBR3,HDCP2.2/CEC/EDID 24K Gold plated Connector, Silver Metal Shell, Black cotton net braid Length:0.5m



CA458



Connector Type: USB Type-C (Male)

to DisplayPort (Male)
Video Resolution: Up to 8K@60Hz
Chip:RTS5459 Housing: Aluminum

Protocol: Compliant with DisplayPort Alt Mode, USB Type-C Specification, and DisplayPort 1.4 Plug & Play: No Driver Required, Hot-Pluggable













VCOM INTERNATIONAL LTD.

Head Quarter

> 8th Floor, No. 12 Dongxuan Road, Huangpu District, Guangzhou City, Guangdong Province, China

Cable & Electronic Factory

>Xiaopenggang Industrial Zone,Longxi Town,Boluo District, Huizhou City, Guangdong Province, China Tel:+86-752-6873123 Fax:+86-752-6873155